







## 1024A Forged Brass Ball Bib Cock with Hose Union (Chrome Plated)

## **Salient Features**

- Screwed Male End to IS 554 / BS 21 / ISO 7.
- Provided with Chrome Plated Brass Ball.
- Sturdy Hose Union provided.
- Chrome Finish.

Test Pressure (Hydrostatic) : Shell : 25 kg/cm<sup>2</sup>g (350 psig) Seat : 16 kg/cm<sup>2</sup>g (225 psig)


Maximum Working Temperature: 220°C

Suitable For Water



## **Materials**

P.No.	Name of Part	<b>Material of Construction</b>	Specification	Quantity
1	Stem	Forged Brass	IS 6912 Gr. FLB	1
2	Nut	Brass (Chrome Plated)		1
3	Lever	Mild Steel		1
4	Gland	Forged Brass	IS 6912 Gr. FLB	1
5	Gland Packing	PTFE		1
6	Thrust Washer	PTFE		1
7	Adaptor	Forged Brass	IS 6912 Gr. FLB	1
8	Ball	Forged Brass (Hard Chrome Plated)	IS 6912 Gr. FLB	1
9	Body Seat Ring	PTFE		2
10	Body	Forged Brass	IS 6912 Gr. FLB	1
11	Sleeve	PVC		1
12	Hose Nut	Forged Brass	IS 6912 Gr. FLB	1
13	Washer	Rubber		1
14	Hose Pipe	Forged Brass	IS 6912 Gr. FLB	1



## **Sizes / Dimensions**

Size (Inches)	Size (mm)	A ~	B ~	С
1/2	15	115	34	1/2″

https://www.zolotovalves.com

~ ±10